

IN THE CLAIMS:

The following is a complete listing of the claims replaces all earlier listings and all earlier versions.

1. 33. (Canceled)

34. (Currently Amended) An image display apparatus, characterized by comprising:

a display panel for displaying an image by irradiation with electrons from an electron source to a fluorescent ~~substances~~ substance;

a scanning circuit for supplying a scanning signal to said display panel;

a modulation circuit for supplying a modulation signal to said display panel;

and

a control circuit for stopping output from said scanning circuit and/or said modulation circuit to said display panel until a signal output from said scanning circuit and/or said modulation circuit to said display panel is determined in starting image display by outputting a signal from said scanning circuit and/or said modulation circuit to said display panel.

35. (Currently Amended) An image display apparatus, characterized by comprising:

a display panel for displaying an image by irradiation with electrons from an electron source to a fluorescent ~~substances~~ substance;

and

a scanning circuit for supplying a scanning signal to said display panel;  
a modulation circuit for supplying a modulation signal to said display panel;

a control circuit for delaying output of a signal from said scanning circuit and/or said modulation circuit to said display panel after a power source is turned on in starting image display by outputting a signal from said scanning circuit and/or said modulation circuit to said display panel,

wherein the signal output from said scanning circuit and/or said modulation circuit to said display panel is determined during the delay time.

36. (Currently Amended) An image display apparatus, characterized by comprising:

a display panel for displaying an image by irradiation with electrons from an electron source to a fluorescent ~~substances~~ substance;

an acceleration potential supply circuit for supplying to said display panel an acceleration potential for accelerating electrons from the electron source;

a scanning circuit for supplying a scanning signal to said display panel;  
a modulation circuit for supplying a modulation signal to said display panel;

and

a control circuit for stopping supply of the acceleration potential until a signal output from said scanning circuit and/or said modulation circuit to said display panel is determined in starting image display by outputting a signal from said scanning circuit and/or said modulation circuit to said display panel.

37. (Currently Amended) An image display apparatus, characterized by comprising:

a display panel for displaying an image by irradiation with electrons from an electron source to a fluorescent ~~substances~~ substance;

an acceleration potential supply circuit for supplying to said display panel an acceleration potential for accelerating electrons from the electron source;

a scanning circuit for supplying a scanning signal to said display panel;

a modulation circuit for supplying a modulation signal to said display panel;

and

a control circuit for delaying supply of the acceleration potential after a power source is turned on in starting image display by outputting a signal from said scanning circuit and/or said modulation circuit to said display panel,

wherein the signal output from said scanning circuit and/or said modulation circuit to said display panel is determined during the delay time.

38. (Currently Amended) An image display apparatus, characterized by comprising:

a display panel for displaying an image by irradiation with electrons from an electron source to a fluorescent ~~substances~~ substance;

a scanning circuit for supplying a scanning signal to said display panel;

a modulation circuit for supplying a modulation signal to said display panel;

and

a control circuit for stopping output from said scanning circuit and/or said modulation circuit to said display panel until a power source voltage of said scanning circuit and/or said modulation circuit reaches a desired value in starting image display by outputting a signal from said scanning circuit and/or said modulation circuit to said display panel.

39. (Currently Amended) An image display apparatus, characterized by comprising:

a display panel for displaying an image by irradiation with electrons from an electron source to a fluorescent ~~substances~~ substance;

a scanning circuit for supplying a scanning signal to said display panel;

a modulation circuit for supplying a modulation signal to said display panel;

and

a control circuit for delaying output of a signal from said scanning circuit and/or said modulation circuit to said display panel after a power source is turned on in starting image display by outputting a signal from said scanning circuit and/or said modulation circuit to said display panel,

wherein a power source voltage of said scanning circuit and/or said modulation circuit reaches a desired value during the delay time.

40. (Currently Amended) An image display apparatus, characterized by comprising:

a display panel for displaying an image by irradiation with electrons from an electron source to a fluorescent ~~substances~~ substance;

an acceleration potential supply circuit for supplying to said display panel an acceleration potential for accelerating electrons from the electron source;

a scanning circuit for supplying a scanning signal to said display panel;

a modulation circuit for supplying a modulation signal to said display panel;

and

a control circuit for stopping supply of the acceleration potential until a power source voltage of said scanning circuit and/or said modulation circuit reaches a desired value in starting image display by outputting a signal from said scanning circuit and/or said modulation circuit to said display panel.

41. (Currently Amended) An image display apparatus, characterized by comprising:

a display panel for displaying an image by irradiation with electrons from an electron source to a fluorescent ~~substances~~ substance;

an acceleration potential supply circuit for supplying to said display panel an acceleration potential for accelerating electrons from the electron source;

a scanning circuit for supplying a scanning signal to said display panel;

a modulation circuit for supplying a modulation signal to said display panel;

and

^ a control circuit for delaying supply of the acceleration potential after a power source is turned on in starting image display by outputting a signal from said scanning circuit and/or said modulation circuit to said display panel, wherein a power source voltage of said scanning circuit and/or said modulation circuit reaches a desired value during the delay time.

42. (Currently Amended) An image display apparatus, characterized by comprising:

a display panel for displaying an image by irradiation with electrons from an electron source to a fluorescent substance substance;

an acceleration potential supply circuit for supplying to said display panel an acceleration potential for accelerating electrons from the electron source;

a scanning circuit for supplying a scanning signal to said display panel;

a modulation circuit for supplying a modulation signal to said display panel;

and

a control circuit for stopping output of a signal from said scanning circuit and/or said modulation circuit to said display panel, and then stopping supply of power to said scanning circuit and/or said modulation circuit in turning off a power source while an image is displayed by outputting a signal from said scanning circuit and/or said modulation circuit to said display panel.

43. (Currently Amended) An image display apparatus, characterized by comprising:

a display panel for displaying an image by irradiation with electrons from an electron source to a fluorescent ~~substances~~ substance;

an acceleration potential supply circuit for supplying to said display panel an acceleration potential for accelerating electrons from the electron source;

a scanning circuit for supplying a scanning signal to said display panel;

a modulation circuit for supplying a modulation signal to said display panel;

and

a control circuit for stopping output of a signal from said scanning circuit and/or said modulation circuit to said display panel, and then stopping supply of power to said scanning circuit and/or said modulation circuit in performing emergency shutdown while an image is displayed by outputting a signal from said scanning circuit and/or said modulation circuit to said display panel.

44. (Currently Amended) An image display apparatus, characterized by comprising:

a display panel for displaying an image by irradiation with electrons from an electron source to a fluorescent ~~substances~~ substance;

an acceleration potential supply circuit for supplying to said display panel an acceleration potential for accelerating electrons from the electron source;

a scanning circuit for supplying a scanning signal to said display panel;

a modulation circuit for supplying a modulation signal to said display panel;

and

a control circuit for stopping output of a signal from said scanning circuit and/or said modulation circuit to said display panel, and then stopping supply of power to said scanning circuit and/or said modulation circuit when a voltage abnormality is observed while an image is displayed by outputting a signal from said scanning circuit and/or said modulation circuit to said display panel.

54B1  
C1  
cont

45. (Currently Amended) An image display apparatus, characterized by comprising:

a display panel for displaying an image by irradiation with electrons from an electron source to a fluorescent ~~substances~~ substance;

an acceleration potential supply circuit for supplying to said display panel an acceleration potential for accelerating electrons from the electron source;

a scanning circuit for supplying a scanning signal to said display panel;

a modulation circuit for supplying a modulation signal to said display panel;

a first power source for supplying power to said acceleration potential supply circuit and/or said scanning circuit and/or said modulation circuit; and

a second power source for supplying power to said scanning circuit and/or said modulation circuit upon an abnormal state.

46. (Original) The image forming apparatus according to claim 45, wherein the abnormal state is emergency shutdown.



47. (Previously Amended) The image forming apparatus according to claim 34, wherein said second power source comprises a capacitor or a battery.

48. (Previously Amended) The image display apparatus according to claim 34, wherein the electron source comprises a plurality of row-direction wiring lines for receiving a scanning signal, a plurality of column-direction wiring lines for receiving a modulation signal, and a plurality of electron-emitting devices connected to the row-direction wiring lines and the column-direction wiring lines.

49. (Previously Amended) The image display apparatus according to claim 34, wherein the acceleration potential for accelerating electrons from the electron source is a potential higher by not less than 500 V than a potential applied to emit electrons in the electron source.

50. (Previously Amended) The image display apparatus according to claim 34, wherein the acceleration potential for accelerating electrons from the electron source is a potential higher by not less than 3,000 V than a potential applied to emit electrons in the electron source.

51. (Previously Amended) The image display apparatus according to claim 34, wherein the acceleration potential for accelerating electrons from the electron source is a potential higher by not less than 5,000 V than a potential applied to emit electrons in the electron source.